

Technical Data Sheet

Metal Access Panels NFR


Product




INSTALLATION

- Prepare a clear trimmed opening in the structure 5mm larger than the panel size. Do NOT include the visible frame flange in this calculation. Flange covers the edge of opening
- Unlock door with key provided and remove door panel from frame
- Offer up frame and press firmly into place checking it is flush and square
- Check which way you want the door to hinge
- Screw fix using suitable fixings through the pre-drilled holes to all four sides of the frame, ensuring no distortion takes place
- Replace door, close and lock panel.
- Fill any gaps between the frame with decorators caulking or suitable filler

PICTURE FRAME



BEADED FRAME



USE

- Light weight metal access panel range for applications where plastic panels are not practical.
- To provide simple, easy access through dry lined walls, ceilings, ducts and units to gain access to concealed plumbing, switches, valves, stopcocks, fuse boxes, controls and connectors

FEATURES & BENEFITS

- Light weight non-fire rated metal access panel available in both picture frame or beaded frame
- Quick release door panel mechanism fully removed the door for maximum access
- Ideal solution for meeting all gas safety inspection access requirements
- Supplied with additional fixing anchors for deeper wall and ceiling installations, up to an additional 50mm
- Hinge door panels with twist lock mechanism
- Quick and easy to install with universal door handle
- Finish allows for painting if required

Product Details

Product sizes	CODE	SIZE
	INFR15	155 x 155mm
	INFR152	155 x 205mm
	INFR20	205 x 205mm
	INFR30	305 x 305mm
	INFR40	450 x 450mm
	INFR55	555 x 555mm
	INFR60	605 x 605mm
	Frame fitting size as per dimensions	
Acoustic	24dB	

Colour	RAL9016 White powder coated texture finish - 20% gloss
Material	Electro galvanised mild steel

