

# Technical Data Sheet

## FireWrap & Firecuff for Ducting

### Product



### USES

To provide fire protection around any plastic duct penetrating a fire compartment in a domestic, commercial or industrial application.

### FEATURES & BENEFITS

- Firewrap & Firecuff has been tested to BSEN1366-3:2009
- Provided 2 hour fire protection
- Firewrap comes with a sealed tag for ease of fitting
- Available for all round or rectangular systems
- Installed at intersection with wall or ceiling and prevents fire entering to next compartment
- Suitable for masonry or partition walls
- Galvanised metal sleeve available for stud walls

### Round Duct Product Specification

SYSTEM 100 ROUND PIPE		
Code	Description	Fire rating
FW100	System 100 - Firewrap & sleeve	2 hours
FC100x150	System 100 - Firecuff	2 hours

SYSTEM 125 ROUND PIPE		
Code	Description	Fire rating
FSK125W	System 125 - Firewrap kit	60 minutes
FSK125F	System 125 - Foiled firewrap kit	2 hours
FC125x280	System 125 - Firecuff	2 hours
FSK125C	System 125 - Firecuff kit	90 minutes

SYSTEM 150 ROUND PIPE		
Code	Description	Fire rating
FSK150C	System 150 - Firecuff kit	90 minutes

### Rectangular Duct Product Specification

SYSTEM 110x54 RECTANGULAR PIPE		
Code	Description	Fire rating
FW110x54	System 100 - Firewrap & Sleeve	2 hours
FC110x54	System 100 - Firecuff	2 hours

SYSTEM 204x60 RECTANGULAR PIPE		
Code	Description	Fire rating
FW204x60	System 204- Firewrap & Sleeve	2 hours
FC204x60	System 204 - Firecuff	2 hours

SYSTEM 220x90 RECTANGULAR PIPE		
Code	Description	Fire rating
FW220x90	System 220 - Firewrap & Sleeve	60 minutes
FC220x90	System 220 - Firecuff	90 minutes



**Firecuff**

