

# Technical Data Sheet

## PVC Coated & Galvanised Banding

### Product



PVC Coated  
Galvanised Banding

### INSTALLATION

- Fixing: Galvanised banding comes with perforated holes allowing for multiple fixings points.
- Use 3.75 x 30mm long square twisted sherardised nails, screws or bolts. Appropriate fixings should be used to allow for different surfaces
- Not to be used below ground.



### USES

Metal Galvanised banding for use with all standard and insulated ducting. Use PVC coated banding for resistance against heat and corrosion.

### FEATURES & BENEFITS

- Available in standard galvanised band or PVC coated banding
- Lightweight and easy to handle
- Durable and totally resistant to decay
- Suitable for new build or Retro-fit
- Pre-punched holes for easy fixing of bolts and screws
- Supplied in 10m roll with external case
- For use with all types of ducting
- Easy to cut and bend
- PVC coating to totally resistant to heat and corrosion

### Product Details

GLAVBAND PVC	
Size	12mm x 10m roll
Box Quantity	Box of 10 cardboard cases
Colour	Black
Code	GLAVBANDPVC

GLAVBAND	
Size	12mm x 10m reels
Box Quantity	Box of 10 plastic reels
Colour	Galvanised
Code	GLAVBAND

