

Technical Data Sheet

ITG3 Concrete Tile vent

PRODUCT



INSTALLATION


1. Select ventilator position between rafters. Mark opening and cut diagonally corner to corner and fold back. Make a slit above opening and slide Underlay protector.




2. On smaller tiles the batten may need to be cut to allow for the ventilator. Shorter lengths of batten may be fixed above or below the opening for additional support.



3. Lay and fix tiles overlapping the tile vent on each side, using the clip on the right side of the vent to connect to the concrete tile.



4. Secure tile vent to batten by carefully nailing through hole provided. Continue tiling in the normal way.



USES

- For tile roof ventilation, soil vent pipes or mechanical extract ventilation (with accessories)
- For remedial work on existing roofs
- Suitable for roof pitches between 20° and 60°
- For use at low level where the roof construction does not allow eaves or ridge vents
- Can be used at high level in conjunction with G5 at low level.

FEATURES & BENEFITS

- Low profile cowl mirrors the popular G5 on a smaller scale.
- Colour matched with UV stable surface treatment
- Efficient, unobtrusive and easy to install
- Underlay opening protector supplied to maintain the function of the underlay
- Integral 4mm insect screen
- Complies with current Building Regulations; BS5250 & BS5534, ICP2
- Manufactured from ABS and VO fire retardant material for high quality finish and robust construction

Product Details

Free Area	IVTG3—10,000mm ² per vent	
Size	To suit concrete tile profile	
Material	Manufactured from ABS & VO fire retardant material	
Colour	To suit tile	
Code	ITG3	
IVTG3 Airflow resistance when used as SVP	54m ³ /hr (15 lt/sec)	10Pa
	108m ³ /hr (30lt/sec)	42Pa
	216m ³ /hr (60lt/sec)	162Pa

