

Technical Data Sheet


15K Universal Tile vent

PRODUCT




INSTALLATION


1. Position the vent tile directly in line with tile below. Use tile vent to mark position of hole. Cut the felt diagonally in a cross shape and pin to back of rafters.



2. Position the vent into the cut hole. All tile vents must be mechanically fixed down. Lay tile on both sides of the base one nailed down. Remove protective tape and dress around the tiles.



3. Once tile vent is dressed to the tile, clip the cap onto the base securely. Carry on tiling up the roof.



USES

- For tile roof ventilation, soil vent pipes or mechanical extract ventilation (with accessories)
- For remedial work on existing roofs
- Suitable for roof pitches between 17.5° and 60°
- For use at high level or low level where the roof construction does not allow eaves or ridge vents

FEATURES & BENEFITS

- Universal design suits all single lap interlocking roof tiles.
- Low profile design
- Choice of four colours
- Wind tunnel tested
- Adaptor available for soil ventilation or mechanical extraction
- Efficient, unobtrusive and easy to install
- Complies with current Building Regulations; BS5250 & BS5534, ICP2

Product Details

Free Area	15,000mm ² per vent	
Size	Universal	
Material	Soft and Rigid UPVC	
Colour/code	Antique red	985403
	Brown	985436
	Slate Grey	985430
	Terracotta	985434
Airflow resistance when used as SVP (100mm pipe)	15 litres/sec	3.5 Pascals
	30 litres/sec	14 Pascals
	60 litres/sec	56 Pascals

