

MA Shutter Series

Axial fan with automatic louvre shutter
with air capacity up to 345m³/h

Product



Shutter closed



Shutter open


USES


- Continuous or period exhaust ventilation of wet room
- Compatible with Ø100, 125 and 150mm air ducts
- Low to medium air flow motion for short distance


FEATURES & BENEFITS


- Modern design with automatic shutters
- Casing and impeller are made of high quality, durable ABS plastic which is UV resistant
- Fitted with thermal actuator, providing smooth opening and closing of the automatic shutter
- Equipped with over heating protection
- Protection Rated IP24
- Maintenance free bearings for 40,000hrs operation

MODIFICATIONS & OPTIONS


 **MA L** - The motor is equipped with ball bearings for long service life (approx. 40,000 hrs). The bearings are maintenance free and contain enough grease for the entire operating period.

 **MA T** - Equipped with a regulated timer with the operation time from 2 to 30 minutes.

 **MA TH** - Equipped with timer and humidity sensor with threshold value form 60 to 90%.


 **Quite V** - Can be fitted with a Pull Cord switch.

 **MA Turbo** - High powered motor

 **MA Press** - 5 blade low noise impeller with improved aerodynamics for higher fan capacity

DIMENSION

MODEL	Dimension (mm)				
	ØD	B	H	L	L1
MA100	100	165	150	92	32
MA125	125	190	173	98	33
MA150	150	212	195	114	33



TECHNICAL DATA

MODEL	Voltage (V) at 50 Hz	Power Consumption (W)	Current (A)	Maximum air capacity (m ³ /h)	Sound Pressure Level at 3m (dB(A))	Weight (kg)	R.P.M
MA100	220-240	18	0.085	98	34	0.65	2300
MA125	220-240	22	0.10	185	35	0.75	2400
MA150	220-240	26	0.13	295	39	1.02	2400



IP 24

